

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rzędowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
270/95R32 136D 150A2 Performer 95	275	1327	628	4092	W9	W8, W10

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)								
	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		2480	2655	2835	3005	3200	3410	3610	3810
10	2180	2380	2560	2765	3000	3180	3350		
25	1725	1885	2030	2195	2375	2520	2655		
30	1675	1835	1970	2130	2305	2445	2580		
40	1595	1745	1875	2025	2195	2330	2455		
50	1530	1675	1800	1945	2105	2235	2355		
65	1460	1595	1715	1850	2005	2125	2240		

(*) : Cyclic Application (see note)

Note: * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
 * Vehicles must be unloaded before transport outside the field.
 * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
 * Maximum load per tyre includes all possible field and vehicle/usage variations.
 * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
 * Basic inflation pressure must be increased as per tables.