

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rzędowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
270/95R36 139D 153A2 Performer 95	275	1428	675	4390	W9	W8, W10

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)								
	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		2625	2810	2990	3195	3430	3650	3875	4135
10	2315	2535	2725	2990	3195	3430	3650		
25	1830	2000	2150	2360	2520	2705	2880		
30	1775	1940	2085	2290	2445	2625	2795		
40	1690	1850	1990	2180	2330	2500	2665		
50	1620	1770	1905	2090	2235	2400	2555		
65	1545	1685	1815	1990	2125	2285	2430		

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.