

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rządowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
270/95R48 144D 158A2 Performer 95	275	1733	819	5332	W9	W8, W10

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)								
	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		3055	3270	3510	3805	4035	4260	4515	4760
10	2720	2975	3200	3510	3805	4035	4250		
25	2125	2325	2500	2740	2970	3150	3320		
30	2065	2255	2425	2660	2880	3055	3220		
40	1965	2150	2310	2535	2745	2910	3070		
50	1885	2060	2215	2430	2630	2790	2940		
65	1795	1960	2110	2315	2505	2660	2800		

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.