

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rzędowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
300/95R42 147D 161A2 Performer 95	306	1637	774	5048	W10	W9, DW10, DW11, W11

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)								
	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		3300	3560	3830	4095	4365	4625	4930	5230
10	2910	3220	3495	3805	4095	4365	4625		
25	2295	2535	2755	2995	3225	3440	3645		
30	2230	2465	2675	2910	3130	3340	3540		
40	2120	2345	2545	2770	2980	3180	3370		
50	2035	2250	2440	2655	2860	3050	3230		
65	1935	2140	2325	2530	2720	2905	3075		

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.