

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rzędowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
300/95R52 151D 165A2 Performer 95	302	1893	894	5832	W10	W9, DW10, DW11, W11

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)								
	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		3735	4000	4270	4530	4835	5150	5505	5865
10	3275	3580	3850	4160	4505	4835	5150		
25	2600	2845	3060	3305	3580	3840	4090		
30	2525	2760	2970	3205	3475	3725	3970		
40	2405	2630	2825	3055	3305	3550	3780		
50	2305	2520	2710	2925	3170	3405	3625		
65	2195	2400	2580	2790	3020	3240	3450		

(*) : Cyclic Application (see note)

Note: * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
 * Vehicles must be unloaded before transport outside the field.
 * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
 * Maximum load per tyre includes all possible field and vehicle/usage variations.
 * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
 * Basic inflation pressure must be increased as per tables.