

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rzędowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
320/90R32 134D 148A2 Performer 90	310	1391	657	4264	W10	W9, W11

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)											
	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0
10*		1930	2190	2440	2680	2855	3070	3180	3295	3405	3505	3605
10	1650	1930	2190	2440	2680	2810	2930	3045	3150			
25	1315	1540	1750	1945	2140	2240	2335	2430	2515			
30	1280	1495	1695	1890	2075	2175	2270	2355	2440			
40	1220	1425	1615	1800	1975	2070	2160	2245	2325			
50	1170	1365	1550	1725	1895	1985	2070	2150	2230			
65	1110	1300	1475	1645	1805	1890	1970	2050	2120			

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.