

QH711



SOLUTION

Application for tractor, harvester, sprayer



R-1W



- **Improved traction.**

The new developed tread with richer patterns and wider width bring more strength to your agricultural machines and enhance efficiency for your work.

- **Longer tire lifetime.**

Forerunner developed a high-performance rubber compound and significant strong structure. With this advantages, the tire will last for a longer lifetime and save much more cost.

Forerunner's tire radial structure with wider tread can effectively reduce the soil compaction caused by heavy agricultural machines.

- **Less soil compaction.**

SIZE	SERVICE DESCRIPTION LI/SS	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STANDARD RIM	MAX LOAD (KG/LBS)	INFLATE PRESSURE (KPA/PSI)
38'						
460/85R38 (18.4R38)	149A8/146B	1747	455	W14L	3250/7165	160/23

Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rim	Max Speed km/h	Tire Load Capacity (kg) at Tire Inflation Pressure (bar)					
									0,6	0,8	1,0	1,2	1,4	1,6
149/146	A8/B	1747	455	785	5161	825	W14L	10	2780	3125	3420	3710	3980	4225
								30	2290	2535	2775	3010	3245	3480
								40		2365	2590	2810	3030	3250
								50			2360	2560	2760	3000