

QH711



SOLUTION

Application for tractor, harvester, sprayer



R-1W



- **Improved traction.**

The new developed tread with richer patterns and wider width bring more strength to your agricultural machines and enhance efficiency for your work.

- **Longer tire lifetime.**

Forerunner developed a high-performance rubber compound and significant strong structure. With this advantages, the tire will last for a longer lifetime and save much more cost.

Forerunner's tire radial structure with wider tread can effectively reduce the soil compaction caused by heavy agricultural machines.

- **Less soil compaction.**

SIZE	SERVICE DESCRIPTION LI/SS	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STANDARD RIM	MAX LOAD (KG/LBS)	INFLATE PRESSURE (KPA/PSI)
38'						
460/85R38 (18.4R38)	149A8/146B	1747	455	W14L	3250/7165	160/23

Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rim	Max Speed km/h	Tire Load Capacity (kg) at Tire Inflation Pressure (bar)					
									0,6	0,8	1,0	1,2	1,4	1,6
145/142	A8/D	1413	550	631	4155	675	W18L	10	2095	2415	2740	3030	3320	3600
								30	1770	2045	2320	2560	2805	3050
								40	1685	1945	2210	2440	2670	2900
								50	1865	2115	2340	2560	2785	
								65		2015	2230	2440	2650	