

# QH711

## SOLUTION

Application for tractor, harvester, sprayer



**R-1W**



- **Improved traction.**

The new developed tread with richer patterns and wider width bring more strength to your agricultural machines and enhance efficiency for your work.

- **Longer tire lifetime.**

Forerunner developed a high-performance rubber compound and significant strong structure. With this advantages, the tire will last for a longer lifetime and save much more cost.

Forerunner's tire radial structure with wider tread can effectively reduce the soil compaction caused by heavy agricultural machines.

- **Less soil compaction.**

SIZE	SERVICE DESCRIPTION LI/SS	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STANDARD RIM	MAX LOAD (KG/LBS)	INFLATE PRESSURE (KPA/PSI)
<b>28'</b>						
540/65R28	152A8/149D	1413	550	W18L	3550/7826	240/35

Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rim	Max Speed km/h	Tire Load Capacity (kg) at Tire Inflation Pressure (bar)							
									0,6	0,8	1,0	1,2	1,4	1,6	2,0	2,4
152/149	A8/D	1413	550	631	4155	675	W18L	10	2095	2440	2745	3050	3355	3615	4010	4355
								30	1800	2095	2360	2620	2880	3105	3445	3740
								40	1705	1990	2240	2485	2735	2950	3270	3550
								50		1915	2155	2395	2630	2835	3145	3415
								65			2050	2275	2505	2700	2990	3250