

QH711



SOLUTION

Application for tractor, harvester, sprayer



R-1W



- **Improved traction.**

The new developed tread with richer patterns and wider width bring more strength to your agricultural machines and enhance efficiency for your work.

- **Longer tire lifetime.**

Forerunner developed a high-performance rubber compound and significant strong structure. With this advantages, the tire will last for a longer lifetime and save much more cost.

Forerunner's tire radial structure with wider tread can effectively reduce the soil compaction caused by heavy agricultural machines.

- **Less soil compaction.**

SIZE	SERVICE DESCRIPTION LI/SS	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STANDARD RIM	MAX LOAD (KG/LBS)	INFLATE PRESSURE (KPA/PSI)
30'						
540/65R30	153A8/150D	1464	550	W18L	3650/8057	240/35

Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rim	Max Speed km/h	Tire Load Capacity (kg) at Tire Inflation Pressure (bar)							
									0,6	0,8	1,2	1,6	1,8	2,0	2,2	2,4
153/150	A8/D	1464	550	661	4378	700	W18L	10	2515	2775	3540	4090	4325	4560	4790	5025
								30	1925	2130	2715	3135	3315	3495	3675	3855
								40	1835	2030	2585	2985	3155	3330	3500	3650
								50	1760	1945	2480	2865	3030	3190	3355	3520
								65				2725	2885	3040	3195	3350