

QH711



SOLUTION

Application for tractor, harvester, sprayer



R-1W



- **Improved traction.**

The new developed tread with richer patterns and wider width bring more strength to your agricultural machines and enhance efficiency for your work.

- **Longer tire lifetime.**

Forerunner developed a high-performance rubber compound and significant strong structure. With this advantages, the tire will last for a longer lifetime and save much more cost.

Forerunner's tire radial structure with wider tread can effectively reduce the soil compaction caused by heavy agricultural machines.

- **Less soil compaction.**

SIZE	SERVICE DESCRIPTION LI/SS	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STANDARD RIM	MAX LOAD (KG/LBS)	INFLATE PRESSURE (KPA/PSI)
28'						
600/65R28	147A8/147B	1481	591	W18L	3075/6780	160/23

Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rim	Max Speed km/h	Tire Load Capacity (kg) at Tire Inflation Pressure (bar)					
									0,6	0,8	1,0	1,2	1,4	1,6
147/147	A8/B	1491	591	670	4470	700	W18L	10	2430	2810	3185	3520	3770	4000
								30	2055	2375	2690	2980	3260	3545
								40		2065	2345	2590	2835	3075
								50			2345	2590	2835	3075
								65						