



## SOLUTION

Application for tractor, harvester, sprayer



**R-1W**



- **Improved traction.**

The new developed tread with richer patterns and wider width bring more strength to your agricultural machines and enhance efficiency for your work.

- **Longer tire lifetime.**

Forerunner developed a high-performance rubber compound and significant strong structure. With this advantages, the tire will last for a longer lifetime and save much more cost.

Forerunner's tire radial structure with wider tread can effectively reduce the soil compaction caused by heavy agricultural machines.

- **Less soil compaction.**

SIZE	SERVICE DESCRIPTION LI/SS	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STANDARD RIM	MAX LOAD (KG/LBS)	INFLATE PRESSURE (KPA/PSI)
<b>42'</b>						
650/65R42	168A8/165D	1913	645	DW20A	5150/11354	240/35
	170A8/167D	1913	645	DW20A	6000/13228	320/46

Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rim	Max Speed km/h	Tire Load Capacity (kg) at Tire Inflation Pressure (bar)					
									1,2	1,6	2,0	2,4	2,8	3,2
170/167	A8/D	1913	645	868	5681	925	DW20A	10	3520	4350	5100	5920	6675	7500
								30	2930	3615	4235	4925	5550	6235
								40	2815	3480	4075	4740	5340	6000
								50	2765	3415	4000	4650	5240	5885
								65	2560	3160	3705	4305	4850	5450