

# QH711



## SOLUTION

Application for tractor, harvester, sprayer



## R-1W



- **Improved traction.**

The new developed tread with richer patterns and wider width bring more strength to your agricultural machines and enhance efficiency for your work.

- **Longer tire lifetime.**

Forerunner developed a high-performance rubber compound and significant strong structure. With this advantages, the tire will last for a longer lifetime and save much more cost.

Forerunner's tire radial structure with wider tread can effectively reduce the soil compaction caused by heavy agricultural machines.

- **Less soil compaction.**

SIZE	SERVICE DESCRIPTION LI/SS	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STANDARD RIM	MAX LOAD (KG/LBS)	INFLATE PRESSURE (KPA/PSI)
<b>38'</b>						
710/70R38	166A8/166B	1959	716	DW23A	5300/11680	160/23

Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rim	Max Speed km/h	Tire Load Capacity (kg) at Tire Inflation Pressure (bar)					
									0,6	0,8	1,0	1,2	1,4	1,6
166/166	A8/B	1959	716	867	5751	925	DW23A	10	3910	4550	5190	5830	6470	7105
								30	3125	3635	4145	4655	5165	5675
								40	3395	3870	4350	4825	5300	
								50		3870	4350	4825	5300	