

QH711



SOLUTION

Application for tractor, harvester, sprayer



R-1W



- **Improved traction.**

The new developed tread with richer patterns and wider width bring more strength to your agricultural machines and enhance efficiency for your work.

- **Longer tire lifetime.**

Forerunner developed a high-performance rubber compound and significant strong structure. With this advantages, the tire will last for a longer lifetime and save much more cost.

Forerunner's tire radial structure with wider tread can effectively reduce the soil compaction caused by heavy agricultural machines.

- **Less soil compaction.**

SIZE	SERVICE DESCRIPTION LI/SS	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STANDARD RIM	MAX LOAD (KG/LBS)	INFLATE PRESSURE (KPA/PSI)
42'						
710/70R42	171A8/168D	2061	716	DW23A	5600/12345	160/23

Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rim	Max Speed km/h	Tire Load Capacity (kg) at Tire Inflation Pressure (bar)					
									0,6	0,8	1,0	1,2	1,4	1,6
171/168	A8/D	2061	716	918	6121	975	DW23A	10	4075	5410	6035	6565	7210	7850
								30	3350	4450	4965	5400	5930	6455
								40	3195	4240	4730	5145	5650	6150
								50	3680	4100	4465	4900	5335	
								65			4305	4685	5145	5600