

# QH711



## SOLUTION

Application for tractor, harvester, sprayer



## R-1W



- **Improved traction.**

The new developed tread with richer patterns and wider width bring more strength to your agricultural machines and enhance efficiency for your work.

- **Longer tire lifetime.**

Forerunner developed a high-performance rubber compound and significant strong structure. With this advantages, the tire will last for a longer lifetime and save much more cost.

Forerunner's tire radial structure with wider tread can effectively reduce the soil compaction caused by heavy agricultural machines.

- **Less soil compaction.**

SIZE	SERVICE DESCRIPTION LI/SS	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	STANDARD RIM	MAX LOAD (KG/LBS)	INFLATE PRESSURE (KPA/PSI)
<b>32'</b>						
800/65R32	178A8/178B	1853	798	DW25A	7500/16534	320/46

Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rim	Max Speed km/h	Tire Load Capacity (kg) at Tire Inflation Pressure (bar)								
									0,6	0,8	1,0	1,4	1,6	2,0	2,4	2,8	3,2
178/178	A8/B	1853	798	817	5503	875	DW25A	10	4425	5160	5895	7260	7875	8775	9960	10350	11250
								30	3155	3680	4205	5175	5610	6260	7105	7380	8025
								40	3440	3930	4840	5250	5850	6640	6900	7500	
								50		3930	4840	5250	5850	6640	6900	7500	