



**GALAXY
AGRICULTURE**

TRA: **R-1W**
Speed Rating: **D**

TL
TUBE LESS

Earth Pro radial 650 is an extra wide tire available in radial for use in agricultural tractors and combine harvesters for farming. It is characterized by increased load capacity for the same inflation pressure. This means that the low inflation pressure combined with large footprint helps reduce soil compaction. Low angled lugs of the tire at the shoulder area improve traction, while higher angles around the tire center line improve ride comfort. This leads to increased tire traction efficiency by an effective traction/slip characteristic. Also the strong radial construction with reinforced beads and sidewalls provide long tire life.

TRACTOR - 600/65R28

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load																										
								Speed																										
1)Not high and sustained torque,2)Road Transport																																		
Non cyclic operation																																		
Field kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph	70 kmph	Field kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph	70 kmph															
600/65R28	W18L W16L	591	1480	669	4461	154D 157A8	1.2	2880	3750	3350	3080	2960	2880	2740	2630	2500	2280																	
							1.6	3400	4440	3970	3640	3510	3400	3240	3110	2960	2690																	
							2	3880	5060	4520	4150	3990	3880	3690	3540	3370	3070																	
							2.4	4310	5630	5030	4610	4440	4310	4110	3940	3750	3410																	

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load														
								Speed														
1)Not high and sustained torque,2)Road Transport																						
Cyclic operation																						
10 kmph	15 kmph	10 kmph	15 kmph	10 kmph	15 kmph	10 kmph	15 kmph	10 kmph	15 kmph	10 kmph	15 kmph											
600/65R28	W18L W16L	591	1480	669	4461	154D 157A8	1.5	4250	5030	4730	3880											
							2	5030	5730	5430	4590											
							2.5	5730	6430	6130	5220											
							3	6380	7080	6780	5810											

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

