



**GALAXY
AGRICULTURE**

TRA: R-1
Speed Rating: A8



TUBE TYPE

Optimised 45 degree lug angle ensures good roadability while on the road and superior self cleaning in the field. Tire life is enhanced by compound designed for low wear, additional rubber at lug centre, stabilised lugs at centre by evenly distributed tie bar. Specially designed lug angles and radius prevents lug base cracks. Additional rubber layer improves penetration resistance. Tougher sidewall provides deflection stability and protection from external damages.

TRACTOR - 9.5-24

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load											
								Speed											
		Drive Wheel Application							Static kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph				
		SW mm	OD mm	8 3175 112A8	8 3175 112A8	8 3175 112A8	8 3175 112A8	0.8	1240	810	720	660	600	580	540				
9.5-24	8							1.2	1560	1020	910	840	750	730	680				
								1.6	1860	1220	1090	1000	900	870	810				
								2	2120	1380	1230	1130	1020	980	920				
								2.4	2350	1530	1370	1250	1130	1090	1020				
								2.8	2580	1680	1500	1380	1240	1200	1120				

