



12.4-32

Sure Grip All Service • 115A8 • R-1



TECHNICAL DATA

Design	Sure Grip All Service	Static Loaded Radius mm	611*
Industry Classification	R-1	Rolling Circ mm	4071*
Tyre Size	12.4-32	SRI	n/a
LI/SS	115A8	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	170*
PR	6	Max Load kg	1215*
TL/TT	TT	Tread Depth mm	n/a
Section Width mm	315*	Recom'd Rim	W11
Overall Diameter mm	1360*	Other approved rims	n/a

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	80kpa	100kpa	140kpa	150kpa	170kpa	180kpa	190kpa	210kpa	220kpa	250kpa	280kpa
40	825*	900*	1090*	1150*	1215†	n/a	n/a	n/a	n/a	n/a	n/a
25	915*	1000*	1210*	1280*	1350*	n/a	n/a	n/a	n/a	n/a	n/a

* Measurements are estimates.

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor