



# 12.5/80-18

Sure Grip Lug • 143A8 • R-4/I-3



## TECHNICAL DATA

|                         |               |                                |      |
|-------------------------|---------------|--------------------------------|------|
| Design                  | Sure Grip Lug | Static Loaded Radius mm        | n/a  |
| Industry Classification | R-4/I-3       | Rolling Circ mm                | n/a  |
| Tyre Size               | 12.5/80-18    | SRI                            | n/a  |
| LI/SS                   | 143A8         | Weight kg                      | n/a  |
| FR/DW                   | FR            | Nominal Inflation Pressure kPa | 430  |
| PR                      | 14            | Max Load kg                    | 2725 |
| TL/TT                   | TL            | Tread Depth mm                 | n/a  |
| Section Width mm        | 308*          | Recom'd Rim                    | W9   |
| Overall Diameter mm     | 965*          | Other approved rims            | n/a  |

## LOAD DATA

| Max Speed (km/h) | Tyre load (kg) at various inflation pressures (kPa) |        |        |        |        |        |        |        |        |        |        |
|------------------|-----------------------------------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
|                  | 150kpa                                              | 170kpa | 190kpa | 230kpa | 250kpa | 280kpa | 300kpa | 330kpa | 350kpa | 370kpa | 430kpa |
| 40               | 1450                                                | 1550   | 1600   | 1800   | 1900   | 2000   | 2120   | 2240   | 2300   | 2430   | 2725   |

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor