



380/85R24

Optitrac • 131D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	562
Industry Classification	R-1W	Rolling Circ mm	3769
Tyre Size	380/85R24	SRI	600
LI/SS	131D	Weight kg	75
FR/DW	n/a	Nominal Inflation Pressure kPa	160
PR	n/a	Max Load kg	1950
TL/TT	TL	Tread Depth mm	40
Section Width mm	374	Recom'd Rim	W12
Overall Diameter mm	1250	Other approved rims	W13, W11

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	220kpa	240kpa	260kpa
70	n/a	1145	1285	1450	1600	1775	n/a	n/a	n/a	n/a	n/a
65	n/a	1250	1400	1600	1750	1950†	n/a	n/a	n/a	n/a	n/a
50	n/a	1315	1470	1680	1840	2050	n/a	n/a	n/a	n/a	n/a
40	n/a	1370	1535	1750	1915	2135	n/a	n/a	n/a	n/a	n/a
30	1220	1440	1610	1840	2010	2245	n/a	n/a	n/a	n/a	n/a
10	1590	1875	2100	2400	2625	2925	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	2125	2595	2775	2955	3135	3315	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor