



380/85R28

Optitrac • 133D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	609
Industry Classification	R-1W	Rolling Circ mm	4080
Tyre Size	380/85R28	SRI	650
LI/SS	133D	Weight kg	94
FR/DW	n/a	Nominal Inflation Pressure kPa	160
PR	n/a	Max Load kg	2060
TL/TT	TL	Tread Depth mm	46
Section Width mm	388	Recom'd Rim	W12
Overall Diameter mm	1353	Other approved rims	W13, W11

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	220kpa	240kpa	260kpa
70	n/a	1205	1285	1450	1600	1875	n/a	n/a	n/a	n/a	n/a
65	n/a	1320	1500	1700	1900	2060†	n/a	n/a	n/a	n/a	n/a
50	n/a	1385	1575	1785	1995	2165	n/a	n/a	n/a	n/a	n/a
40	n/a	1445	1645	1860	2080	2255	n/a	n/a	n/a	n/a	n/a
30	1325	1520	1725	1955	2185	2370	n/a	n/a	n/a	n/a	n/a
10	1725	1980	2250	2550	2850	3090	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	2245	2740	2930	3120	3310	3500	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor