



380/85R30

Optitrac • 135D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	633
Industry Classification	R-1W	Rolling Circ mm	4226
Tyre Size	380/85R30	SRI	675
LI/SS	135D	Weight kg	102
FR/DW	n/a	Nominal Inflation Pressure kPa	160
PR	n/a	Max Load kg	2180
TL/TT	TL	Tread Depth mm	46
Section Width mm	391	Recom'd Rim	W12
Overall Diameter mm	1399	Other approved rims	W13, W11

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	220kpa	240kpa	260kpa
70	n/a	1245	1285	1450	1600	1985	n/a	n/a	n/a	n/a	n/a
65	n/a	1360	1550	1750	1950	2180†	n/a	n/a	n/a	n/a	n/a
50	n/a	1430	1630	1840	2050	2290	n/a	n/a	n/a	n/a	n/a
40	n/a	1490	1695	1915	2135	2385	n/a	n/a	n/a	n/a	n/a
30	1355	1565	1780	2010	2245	2505	n/a	n/a	n/a	n/a	n/a
10	1770	2040	2325	2625	2925	3270	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	2310	2900	3100	3300	3505	3705	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor