



380/85R34

Optitrac • 137D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	676
Industry Classification	R-1W	Rolling Circ mm	4532
Tyre Size	380/85R34	SRI	725
LI/SS	137D	Weight kg	108
FR/DW	n/a	Nominal Inflation Pressure kPa	160
PR	n/a	Max Load kg	2300
TL/TT	TL	Tread Depth mm	46
Section Width mm	393	Recom'd Rim	W12
Overall Diameter mm	1503	Other approved rims	W13, W11

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	220kpa	240kpa	260kpa
70	n/a	1325	1285	1450	1600	2095	n/a	n/a	n/a	n/a	n/a
65	n/a	1450	1650	1850	2060	2300†	n/a	n/a	n/a	n/a	n/a
50	n/a	1525	1735	1945	2165	2415	n/a	n/a	n/a	n/a	n/a
40	n/a	1590	1805	2025	2255	2520	n/a	n/a	n/a	n/a	n/a
30	1440	1665	1895	2130	2370	2645	n/a	n/a	n/a	n/a	n/a
10	1875	2175	2475	2775	3090	3450	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	2465	3060	3275	3485	3700	3910	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor