



460/70R24

IT420 • 159A8/B • R-4



TECHNICAL DATA

Design	IT420	Static Loaded Radius mm	561*
Industry Classification	R-4	Rolling Circ mm	3739*
Tyre Size	460/70R24	SRI	600*
LI/SS	159A8/B	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	400
PR	n/a	Max Load kg	4375
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	474*	Recom'd Rim	W14
Overall Diameter mm	1250*	Other approved rims	W15L, W16L

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	140kpa	180kpa	200kpa	220kpa	240kpa	260kpa	280kpa	300kpa	320kpa	360kpa	400kpa
50	1900	2240	2430	2650	2800	3000	3250	3450	3550	4000	4375†
40	1900	2240	2430	2650	2800	3000	3250	3450	3550	4000	4375
30	1975	2330	2525	2755	2910	3120	3380	3590	3690	4160	4550
15cycl	2545	3000	3255	3550	3750	4020	4355	4625	4755	5360	5865
10cycl	2850	3360	3645	3975	4200	4500	4875	5175	5325	6000	6565

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor