



# 460/85R30

Optitrac • 145B • R-1W



## TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	686
Industry Classification	R-1W	Rolling Circ mm	4572
Tyre Size	460/85R30	SRI	725
LI/SS	145B	Weight kg	142.94
FR/DW	n/a	Nominal Inflation Pressure kPa	160
PR	n/a	Max Load kg	2900
TL/TT	TL	Tread Depth mm	50.8
Section Width mm	475	Recom'd Rim	W15L
Overall Diameter mm	1542	Other approved rims	W14L, W16L

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	220kpa	240kpa	260kpa
50	n/a	1850	2120	2360	2650	2900	n/a	n/a	n/a	n/a	n/a
40	1600	1850	2120	2360	2650	2900†	n/a	n/a	n/a	n/a	n/a
30	1790	2070	2375	2645	2970	3250	n/a	n/a	n/a	n/a	n/a
10	2400	2775	3180	3540	3975	4350	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	3145	3860	4125	4395	4665	4930	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor