



460/85R34

Optitrac • 147D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	742
Industry Classification	R-1W	Rolling Circ mm	5010
Tyre Size	460/85R34	SRI	775
LI/SS	147D	Weight kg	146
FR/DW	n/a	Nominal Inflation Pressure kPa	160
PR	n/a	Max Load kg	3075
TL/TT	TL	Tread Depth mm	46
Section Width mm	467	Recom'd Rim	W15L
Overall Diameter mm	1659	Other approved rims	W14L, W16L,

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	220kpa	240kpa	260kpa
70	n/a	1780	2045	2285	2560	2810	n/a	n/a	n/a	n/a	n/a
65	n/a	1950	2240	2500	2800	3075†	n/a	n/a	n/a	n/a	n/a
50	n/a	2050	2350	2625	2940	3230	n/a	n/a	n/a	n/a	n/a
40	n/a	2135	2455	2740	3065	3365	n/a	n/a	n/a	n/a	n/a
30	1895	2245	2575	2875	3220	3535	n/a	n/a	n/a	n/a	n/a
10	2475	2925	3360	3750	4200	4615	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	3315	4095	4380	4660	4950	5230	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor