



480/70R28

Optitrac • 140D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	636*
Industry Classification	R-1W	Rolling Circ mm	4241*
Tyre Size	480/70R28	SRI	675*
LI/SS	140D	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	160*
PR	n/a	Max Load kg	2500*
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	503*	Recom'd Rim	W15L
Overall Diameter mm	1421*	Other approved rims	W14L, W16L

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	120kpa	140kpa	160kpa	200kpa	220kpa	240kpa	280kpa	300kpa	320kpa
70	n/a	1455	2370	2095	2275	n/a	n/a	n/a	n/a	n/a	n/a
65	1360	1600	2606	2300	2500†	n/a	n/a	n/a	n/a	n/a	n/a
50	n/a	1680	2735	2415	2625	n/a	n/a	n/a	n/a	n/a	n/a
40	n/a	1750	2855	2520	2740	n/a	n/a	n/a	n/a	n/a	n/a
30	1565	1840	2995	2645	2875	n/a	n/a	n/a	n/a	n/a	n/a
10	2040	2400	3910	3450	3750	n/a	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	3330	3555	3785	4250	n/a	n/a	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor