



540/65R28

Optitrac • 142D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	633*
Industry Classification	R-1W	Rolling Circ mm	4218*
Tyre Size	540/65R28	SRI	675*
LI/SS	142D	Weight kg	n/a
FR/DW	n/a	Nominal Inflation Pressure kPa	160*
PR	n/a	Max Load kg	2650*
TL/TT	TL	Tread Depth mm	n/a
Section Width mm	550*	Recom'd Rim	W18L
Overall Diameter mm	1413*	Other approved rims	W16L

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	260kpa	280kpa
70	n/a	1540	1760	1980	2195	2410	n/a	n/a	n/a	n/a	n/a
65	n/a	1695	1935	2175	2410	2650†	n/a	n/a	n/a	n/a	n/a
50	n/a	1780	2030	2285	2530	2785	n/a	n/a	n/a	n/a	n/a
40	n/a	1855	2120	2380	2640	2900	n/a	n/a	n/a	n/a	n/a
30	1725	1950	2225	2500	2770	3045	n/a	n/a	n/a	n/a	n/a
10	2250	2545	2905	3265	3615	3975	n/a	n/a	n/a	n/a	n/a
10cycl	n/a	n/a	2880	3525	3770	4015	4260	4505	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor