



600/65R34

Optitrac • 157D • R-1W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	730
Industry Classification	R-1W	Rolling Circ mm	4901
Tyre Size	600/65R34	SRI	n/a
LI/SS	157D	Weight kg	202
FR/DW	n/a	Nominal Inflation Pressure kPa	240
PR	n/a	Max Load kg	4125
TL/TT	TL	Tread Depth mm	52
Section Width mm	600	Recom'd Rim	DW20B
Overall Diameter mm	1626	Other approved rims	n/a

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	260kpa	280kpa
70	n/a	n/a	2345	2640	2865	3140	3320	3525	3755	n/a	n/a
65	n/a	2240	2575	2900	3150	3450	3650	3875	4125†	n/a	n/a
50	n/a	2350	2705	3045	3310	3625	3835	4070	4330	n/a	n/a
40	n/a	2455	2820	3175	3450	3780	3995	4245	4515	n/a	n/a
30	2245	2575	2960	3335	3620	3965	4200	4455	4745	n/a	n/a
10	2925	3360	3865	4350	4725	5175	5475	5815	6190	n/a	n/a
10cycl	n/a	n/a	3810	4545	5000	5325	5640	5865	6385	6595	6805

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor