



600/70R28

Optitrac • 161B • R1-W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	707
Industry Classification	R1-W	Rolling Circ mm	4721
Tyre Size	600/70R28	SRI	725
LI/SS	161B	Weight kg	196
FR/DW	n/a	Nominal Inflation Pressure kPa	280
PR	n/a	Max Load kg	4625
TL/TT	TL	Tread Depth mm	51
Section Width mm	597	Recom'd Rim	DW18L
Overall Diameter mm	1561	Other approved rims	DW20B

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	280kpa	320kpa
50	n/a	n/a	2575	2900	3250	3550	3750	3875	4125	4625	n/a
40	1950	2300	2575	2900	3250	3550	3750	3875	4125	4625†	n/a
30	2085	2460	2755	3105	3480	3800	4015	4145	4415	4950	n/a
10	2925	3450	3865	4350	4875	5325	5625	5815	6190	6940	n/a
10cycl	n/a	n/a	3910	4545	5000	5325	5640	6035	6385	6805	7485

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor