



750/65R26

Optitrac • 166B • R1-W



TECHNICAL DATA

Design	Optitrac	Static Loaded Radius mm	739
Industry Classification	R1-W	Rolling Circ mm	4932
Tyre Size	750/65R26	SRI	775
LI/SS	166B	Weight kg	273
FR/DW	n/a	Nominal Inflation Pressure kPa	240
PR	n/a	Max Load kg	5300
TL/TT	TL	Tread Depth mm	52
Section Width mm	764	Recom'd Rim	DW25B
Overall Diameter mm	1632	Other approved rims	DW23B

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (kPa)										
	60kpa	80kpa	100kpa	120kpa	140kpa	160kpa	180kpa	200kpa	240kpa	280kpa	320kpa
50	n/a	2900	3250	3650	4000	4375	4625	4875	5300	n/a	n/a
40	2430	2900	3250	3650	4000	4375	4625	4875	5300†	n/a	n/a
30	2600	3105	3480	3905	4280	4680	4950	5215	5670	n/a	n/a
10	3645	4350	4875	5475	6000	6565	6940	7315	7950	n/a	n/a
10cycl	n/a	n/a	4930	5840	6425	6840	7245	7440	8200	8740	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor