

SPECIFICATIONS

AGRIXTRA 70 SERIES

FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions mean stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
420/70R24	130A8 / 130B	TL	W13	W12 W14L	42

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rolling Circumference Index	75% of Internal volume (l)
424	1248	554	3732	600	38	179

Max load per tyre (kg) / Inflation pressure (bar)									
		0.6	0.8	1	1.2	1.4	1.6	1.8	1.9
Service Speed (km/h)	10 LT	1715	1890	2060	2230	2405	2575		2850
	30 LT / 10 HT		1490	1625	1760	1895	2035		
	40 & 50		1395	1520	1645	1775	1900		