
 SPECIFICATIONS

AGRIMIXTRA 85 SERIES

FEATURES & BENEFITS:

Advanced lug arrangement designed for high levels of traction in field applications, excellent grip, and relatively quiet running in road applications.

A flexible sidewall and radial carcass construction designed for a comfortable ride and reduced driver fatigue.

A reinforced lug design and belt package for resistance to punctures and damage.

An optimised footprint shape and dimensions enhance stable operation and minimised soil compaction.

Long-wearing compound and optimised lug design for even wear and long life.

Manufactured and finished to a very high standard of quality and presentation.



Size	2nd Size marking	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
320/85R24	12.4R24	122A8 / 122B	TL	W11	W10	41

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	Rolling Circumference Index	75% of Internal volume (l)
329	1154	517	3450	550	37	109

Max load per tyre (kg) / Inflation pressure (bar)									
	(km/h)	0.6	0.8	1	1.2	1.4	1.6	1.8	1.9
Service Speed (km/h)	10 LT	1355	1490	1625	1760	1895	2035		2250
	30 LT / 10 HT		1175	1285	1390	1500	1605		
	40 & 50		1100	1200	1300	1400	1500		