



Nokian TR Forest 13.6-28 10PR – T483150

TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern TR	TT/ TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Forestry Load capacity kg/lbs		Load capacity kg/lbs												Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	kPa	psi	10 km/h	5 mph	10 km/h	5 mph	20 km/h	10 mph	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	mm	32 nds in	mm	32 nds in		
T483150	13.6-28	130 A8 / 127 B	10	FS FOREST	TT	DW12	DW12, DW11, W11, W12	345	13.6	1 310	51.6	609	24.0	3 934	154.9	250	36	2 335	5 150	2 850	6 285	2 335	5 150	2 040	4 495	1 900	4 190	1 730	3 815	33	42	-	-		

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Road 10 km/h / 5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
120	17	1 185	2 610	1 300	2 865	1 390	3 065	1 600	3 525	1 950	4 300	1 600	3 525
160	23	1 450	3 195	1 595	3 515	1 705	3 760	1 960	4 320	2 395	5 280	1 960	4 320
200	29	1 595	3 515	1 750	3 860	1 875	4 135	2 155	4 750	2 625	5 785	2 155	4 750
250	36	1 730	3 815	1 900	4 190	2 040	4 495	2 335	5 150	2 850	6 285	2 335	5 150

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)							
				Water		Salt (CaCl ₂)		Total weight increase			
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs	kg	lbs
210	55	160	40	129	34	66	145	195	430		

TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55105	TR 218 A