



Nokian TR Forest 14.9-24 14PR – T482220

TT = TUBE-TYPE, to be fitted with tube

Product code	Size	LI/SS	PR	Pattern TR	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Forestry Load capacity kg/lbs		Load capacity kg/lbs										Total tread depth		Tread depth measured on top of tie-bar	
								mm	in	mm	in	mm	in	mm	in	mm	in	kPa	psi	10 km/h	5 mph	10 km/h	5 mph	20 km/h	10 mph	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	40 km/h	32 nds
T482220	14.9-24	138 A8 / 134 B	14	FS FOREST	TT	DW13	DW12, W13, W12, W11	378	14.9	1265	49.8	582	22.9	3707	145.9	300	44	2905	6405	3540	7805	2905	6405	2530	5580	2360	5205	2150	4740	44	56	-	-

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation Pressure		Road 50 km/h / 30 mph		Road 40 km/h / 25 mph		Road 30 km/h / 20 mph		Road 20 km/h / 12.5 mph		Road 10 km/h / 5 mph		Forestry service (LT) 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
120	17	1320	2910	1450	3195	1550	3415	1785	3935	2175	4795	1785	3935
160	23	1610	3550	1770	3900	1895	4180	2175	4795	2655	5855	2175	4795
200	29	1770	3900	1945	4290	2080	4585	2390	5270	2920	6435	2390	5270
240	35	1890	4165	2075	4575	2220	4895	2550	5620	3115	6865	2550	5620
280	41	2070	4565	2275	5015	2435	5370	2800	6175	3415	7530	2800	6175
300	44	2150	4740	2360	5205	2530	5580	2905	6405	3540	7805	2905	6405

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
		Water		Salt (CaCl ₂)		Total weight increase			
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
240	65	180	50	148	39	75	165	223	490

TUBES AND VALVES

USE ALWAYS WITH TUBE

Tube product code	Valve tube-type
T55112	TR 218 A