



Nokian TR Multiplus 500/65R28 – T445411

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI/SS	Pattern TR	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Load capacity kg/lbs						Tread depth	
							mm	in	mm	in	mm	in	mm	in	kPa	psi	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	mm	32 nds in
T445411	500/65R28	144 A8/141 B	Multiplus	TL	W15L	W16L, W14L, W13	480	18.9	1 347	53.0	622	24.5	4 055	159.6	240	35	3 000	6 615	2 800	6 175	2 575	5 675	48	61

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation pressure ¹⁾		Road Service 50 km/h / 30 mph		Road Service 40 km/h / 25 mph		Road Service 30 km/h / 20 mph		Pull Service in Forest 10 km/h / 5 mph		Field Service ²⁾ 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
240	35	2 575	5 675	2 800	6 175	3 000	6 615	3 360	7 405	4 200	9 260
160	23	2 060	4 540	2 240	4 940	2 400	5 290	-	-	3 360	7 405
80	12	1 360	3 000	1 500	3 305	1 610	3 550	-	-	2 250	4 960

1) The maximum tire inflation pressure in forestry use is 320 kPa / 46 psi without increase in the load values.
2) For field applications with high and sustained torque, values for road service 30 km/h / 20 mph are applied.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
315	85	235	60	194	51	99	220	293	645

TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	T55097	TR 218 A