



Nokian TR Multiplus 540/65R28 – T445412

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI/SS	Pattern TR	TT/TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Inflation pressure		Load capacity kg/lbs						Tread depth	
							mm	in	mm	in	mm	in	mm	in	kPa	psi	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	mm	32 nds in
T445412	540/65R28	149 A8/146 B	Multiplus	TL	DW16	W15L, W16L, DW18L, W18L	540	21.3	1 413	55.6	653	25.7	4 254	167.5	240	35	3 480	7 670	3 250	7 165	3 000	6 615	51	64

LOAD CAPACITY VALUES FOR FORESTRY USE

Inflation pressure ¹⁾		Road Service 50 km/h / 30 mph		Road Service 40 km/h / 25 mph		Road Service 30 km/h / 20 mph		Pull Service in Forest 10 km/h / 5 mph		Field Service ²⁾ 10 km/h / 5 mph	
kPa	psi	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
240	35	3 000	6 615	3 250	7 165	3 480	7 670	3 900	8 600	4 880	10 760
160	23	2 300	5 070	2 500	5 510	2 680	5 910	-	-	3 750	8 265
80	12	1 550	3 415	1 700	3 750	1 820	4 010	-	-	2 550	5 620

1) The maximum tire inflation pressure in forestry use is 320 kPa / 46 psi without increase in the load values.
2) For field applications with high and sustained torque, values for road service 30 km/h / 20 mph are applied.

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl ₂)		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
390	105	295	80	240	63	122	270	362	800

TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	T545229	TR 218 A