



Nokian TRI 2 600/65R38 – T445445

Product code	Size	LI/SS	Rim TW profile may replace DW	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Speed Radius Index SRI	Maximum inflation pressure		Load capacity kg / lbs								Total tread depth		Tread depth measured on top of tie-bar	
					mm	in	mm	in	mm	in	mm	in		kPa	psi	30 km/h	20 mph	40 km/h	25 mph	50 km/h	30 mph	65 km/h	40 mph	mm	32 nds in	mm	32 nds in
T445445	600/65R38	166 D	DW20B	DW18L	591	23.3	1 745	68.7	790	31.1	5 290	208.3	825	320	46	6 250	13 780	6 000	13 230	5 640	12 435	5 300	11 685	30	38	25	32

LOAD CAPACITY VALUES AT DIFFERENT SPEEDS AND PRESSURES

Constant		0.8 bar	12 psi	1.2 bar	17 psi	1.6 bar	23 psi	2.0 bar	29 psi	2.4 bar	35 psi	3.2 bar	46 psi
km/h	mph	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
0	0	5 160	11 375	6 700	14 770	8 200	18 080	9 500	20 945	10 950	24 140	13 800	30 425
5	2.5	3 260	7 185	4 220	9 305	5 160	11 375	6 000	13 230	6 900	15 210	8 700	19 180
10	5	2 800	6 175	3 640	8 025	4 440	9 790	5 160	11 375	5 940	13 095	7 500	16 535
15	10	2 540	5 600	3 280	7 230	4 020	8 860	4 680	10 320	5 380	11 860	6 800	14 990
20	12.5	2 450	5 400	3 180	7 010	3 880	8 555	4 500	9 920	5 180	11 420	6 550	14 440
25	15	2 380	5 245	3 080	6 790	3 780	8 335	4 380	9 655	5 040	11 110	6 400	14 110
30	20	2 330	5 135	3 020	6 660	3 700	8 155	4 300	9 480	4 940	10 890	6 250	13 780
35	22.5	2 290	5 050	2 960	6 525	3 640	8 025	4 220	9 305	4 860	10 715	6 150	13 560
40	25	2 240	4 940	2 900	6 395	3 550	7 825	4 125	9 095	4 750	10 470	6 000	13 230
45	28	-	-	2 820	6 215	3 460	7 630	4 020	8 860	4 620	10 185	5 820	12 830
50	30	-	-	2 730	6 020	3 340	7 365	3 880	8 555	4 480	9 875	5 640	12 435
65	40	-	-	2 500	5 510	3 075	6 780	3 650	8 045	4 125	9 095	5 300	11 685

LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)							
				Water		Salt (CaCl ₂)		Total weight increase			
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs	kg	lbs
720	190	540	143	443	117	226	500	669	1 475		

TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	T55445	TR 218A