



## Nokian ELS Radial 700/50R26.5 – T445227

TL = TUBELESS, may be fitted with or without tube

Product code	Size	LI / SS	Pattern	TT / TL	Rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		Maximum inflation pressure		Load capacity kg / lbs				Total tread depth	
							mm	in	mm	in	mm	in	mm	in	kPa	psi	40 km/h	25 mph	65 km/h	40 mph	mm	32 nds in
☞ T445227	700/50R26.5	161 D	ELS	TL	AG 24.00	20.00, 24.00	700	27.6	1 373	54.1	625	24.6	4 160	163.8	280	41	6 300	13 890	4 625	10 195	22	28

☞ Production ended

### LOAD CAPACITY VALUES AT DIFFERENT SPEEDS AND PRESSURES

Constant		0.8 bar	12 psi	1.2 bar	17 psi	1.6 bar	23 psi	2.0 bar	29 psi	2.4 bar	35 psi	2.8 bar	41 psi
km/h	mph	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs
10	5	3 820	8 420	4 780	10 540	5 680	12 520	6 400	14 110	7 450	16 425	8 350	18 410
20	12.5	3 500	7 715	4 380	9 655	5 200	11 465	5 860	12 920	6 850	15 100	7 650	16 865
25	15	3 360	7 405	4 200	9 260	4 980	10 980	5 620	12 390	6 550	14 440	7 350	16 205
30	20	3 220	7 100	4 020	8 860	4 760	10 495	5 380	11 860	6 250	13 780	7 000	15 430
40	25	2 890	6 370	3 620	7 980	4 300	9 480	4 840	10 670	5 620	12 390	6 300	13 890
50	30	2 570	5 665	3 220	7 100	3 820	8 420	4 300	9 480	5 000	11 025	5 600	12 345
65	40	2 120	4 675	2 650	5 840	3 150	6 945	3 550	7 825	4 125	9 095	4 625	10 195

### LIQUID AND SALT BALLASTING

Tire volume 100%		Water filling (75%)		Water / salt filling (75% / -30°C / -22°F)					
				Water		Salt (CaCl <sub>2</sub> )		Total weight increase	
l	gal (US)	l	gal (US)	l	gal (US)	kg	lbs	kg	lbs
610	160	460	120	375	100	191	420	567	1 250

### TUBES AND VALVES

Valve tubeless	Tube product code	Valve tube-type
TR 618 A	T55099	TR 218 A