



CAMSO TM R4

DURABLE OFF-ROAD PERFORMANCE

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	SERVICE	APPLICATION	
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.					
400/80-24 IND (15.5/80-24)	-	TL	DW13	-	DW12	1244	409	34	571	3771	162	A8	IND. TRACTOR	CYCLIC
					DW13L	49.0	16.1	43	22.5	148.5				
					DW14L	1244	409	34	571	3771	162	A8	IND. TRACTOR	CONSTANT
					TW13	49.0	16.1	43	22.5	148.5				
440/80-24 IND (16.9-24 16.5/85-24)	-	TL	DW14L	-	DW13	1328	453	33	601	4016	168	A8	IND. TRACTOR	CYCLIC
					DW13L	52.3	17.8	42	23.7	158.1				
					DW15L	1328	453	33	601	4016	168	A8	IND. TRACTOR	CONSTANT
					TW13	52.3	17.8	42	23.7	158.1				
460/70-24 IND (17.5L-24)	-	TL	DW15L	-	DW14L	1264	455	31	578	3789	159	A8	IND. TRACTOR	CYCLIC
					DW16L	49.8	17.9	39	22.8	149.2				
					TW14L	1264	455	31	578	3789	159	A8	IND. TRACTOR	CONSTANT
					TW15L	49.8	17.9	39	22.8	149.2				
18-19.5	16	TL/TT	14.00	-	1117	454	32	505	3352	160	A8	MPT	DRIVE	
					44.0	17.9	40	19.9	132.0					
405/70-20 (16/70-20)	14	TL/TT	13x20	13SDC	1085	403	27	490	3238	154	A8	MPT	FREE	
					42.7	15.9	34	19.3	127.5					
405/70-20 (16/70-20)	14	TL/TT	13x20	13SDC	1085	403	27	490	3238	142	A8	MPT	DRIVE	
					42.7	15.9	34	19.3	127.5					
18-22.5	16	TL/TT	14.00	-	1209	444	35	545	3638	163	A8	MPT	DRIVE	
					47.6	17.5	44	21.5	143.2					

FEATURES

- Stepped tread design
- Tapered tread lugs
- Optimized lug-to-void ratio
- Heavy-duty carcass

BENEFITS

- Enhances tread cleanout for improved traction
- Improves lug stability for even wearing
- Enhances longevity and tread puncture resistance
- Provides excellent stability and side impact resistance

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]											
	STATIC	CREEP	5 km/h* 3 mph	10 km/h** 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph
5.00	10925	-	7935	7125	6365	5845	5275	5085	4895	4750	4560	4325
73	24085	-	17495	15710	14030	12885	11630	11210	10790	10470	10055	9535
5.00	10925	-	6890	5940	5370	5180	5035	4940	4845	4750	4560	4325
73	24085	-	15190	13095	11840	11420	11100	10890	10680	10470	10055	9535
5.00	12880	-	9350	8400	7505	6890	6215	5990	5770	5600	5375	5095
73	28395	-	20615	18520	16545	15190	13700	13205	12720	12345	11850	11230
5.00	12880	-	8120	7000	6330	6105	5935	5825	5710	5600	5375	5095
73	28395	-	17900	15430	13955	13460	13085	12840	12590	12345	11850	11230
4.00	10065	-	7305	6565	5865	5380	4855	4680	4505	4375	4200	3980
58	22190	-	16105	14475	12930	11860	10705	10320	9930	9645	9260	8775
4.00	10065	-	6345	5470	4945	4770	4640	4550	4465	4375	4200	3980
58	22190	-	13990	12060	10900	10515	10230	10030	9845	9645	9260	8775
5.85	7755	6715	6305	5985	5170	-	-	4765	-	4625	-	4490
85	17100	14800	13900	13200	11400	-	-	10500	-	10200	-	9900
3.50	6190	-	-	-	-	-	5250	4990	-	3375	-	4490
50	13650	-	-	-	-	-	11600	11000	-	7450	-	9900
3.50	6230	-	-	-	-	-	3710	3525	-	2385	-	-
50	13750	-	-	-	-	-	8200	7800	-	5250	-	-
4.50	9850	-	-	-	-	-	6825	6485	-	4390	-	-
64	21750	-	-	-	-	-	15050	14300	-	9700	-	-

*Cyclic: One way distance up to 150 m (500 feet) **Cyclic: One way distance up to 600 m (2000 feet)