

Tires for agricultural and special machinery

NORTEC®

NorTec TA-01



For agricultural and special machinery

| Tire size | 710/70R42 | 520/85R42 | |
|--|---|------------------------|----------------|
| Standard name | TS 38.304-181 | TS 38.304-180 | |
| Pattern type | Ground grip | | |
| Tread pattern height in the middle, mm | 55 | 50 | |
| Ply rating | - | - | |
| Tire weight, not more than, kg | 313,9 | 348,7 | |
| Load-bearing capacity index | 176 | 180 | |
| Recommended/additional rim | DW23B | W16/W18 | |
| Outside diameter, mm | 2055±31 | 1950±29 | |
| Tire section width, mm, not more than | 740 | 537 | |
| Static radius, mm | 936±23 | 891±22 | |
| Q, kgf | 7100/ 10650 | 8000/ 12455 | 4750/4750/7125 |
| V, km/h (index) | 65(D)/10(A2) | 40(A8)/50(B) 10(A2) | |
| P _o at Q _{max} , kPa | 235 | 315 | 235 |
| Version | TL | | |
| Application | 710/70R42 drive wheels of NEW HOLLAND FR 9040-9090, CR 9060/9060 harvesters and K-8140 tractors, and other domestic and foreign agricultural vehicles 520/85R42 drive wheels of tractors such as John Deere, Case, New Holland, Valtra, Claas etc. | | |