



BD 65

Harvester

PERFORMANCE INFORMATION

Harvester tire



FEATURES

Long life / Durability

- Durable nylon carcass structure
- Special tread compound harvester
- High resistance against cuts and tread wear with special tread geometry design.

High Traction / Self cleaning

- Special tread geometry, designed differently on center and shoulders.
- Perfect grip/high traction and self-cleaning property

High safety on inclined fields

- Prevention from side rolling / high safety thanks to improved lateral resistance with reinforced sidewall / carcass structure.

SIZES 23.1-26 • 23.1-30 • 20.8-38

Harvester Characteristics of **BD 65**

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
23.1-26	12	TT	153/A6	DW20B	-	587	1605	4910	740	20 / 1.4	4290	3980	3630	3275	3060	2685
										22 / 1.5	4650	4320	3940	3545	3320	2910
										25 / 1.7	5110	4745	4330	3900	3650	3200
	14	TL	156/A6							26 / 1.8	4700	4365	3965	3595	3360	2955
										28 / 1.9	5150	4780	4340	3935	3680	3235
										29 / 2.0	5600	5200	4720	4280	4000	3520
	18	TL	162/A6							32 / 2.2	5565	5245	4760	4315	4035	3550
										35 / 2.4	6090	5740	5210	4720	4415	3885
										38 / 2.6	6550	6175	5605	5080	4750	4180
23.1-30	12	TT	151/A6	DW20B	-	587	1705	5090	770	20 / 1.4	4150	3855	3500	3170	2965	2610
										22 / 1.5	4440	4125	3740	3395	3170	2790
										25 / 1.7	4830	4485	4070	3690	3450	3035
	14	TL	154/A6							26 / 1.8	4410	4095	3715	3365	3150	2770
										28 / 1.9	4830	4485	4070	3685	3450	3035
										29 / 2.0	5250	4875	4425	4010	3750	3300
	18	TL	160/A6							32 / 2.2	5290	4915	4460	4045	3780	3325
										35 / 2.4	5795	5380	4885	4430	4140	3645
										38 / 2.6	6300	5850	5310	4815	4500	3960
20.8-38	14	TT/TL	159/A6	W18L	W16L	528	1840	5550	848	29 / 2.0	5084	4720	4283	3885	3630	3195
										32 / 2.2	5515	5120	4645	4212	3935	3465
										34 / 2.3	6125	5688	5160	4680	4375	3850

Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

* For load capacity on various speed ratings, and inflation figures, please consult your sales representative.

** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.