

IND 15

Grips muddy and rough surfaces; and provides a strong traction. Appropriate tread structure provides what easy control.

Resistant to problems such as cracks, ruptures and stone cuts. Extra thick rubber part in the center of the tread provides long wear life and comfortable drive on hard surfaces.

Deep grooved unidirectional pattern provides powerful traction and self cleaning feature under all conditions.

Strong off-road service mixture provides resistance to cuts, disintegrations, tears and wear.

Strong nylon, cord and frame structure provides high resistance to impacts.



INDUSTRIAL TRACTION IND 15

| TIRE SIZE | PR | TT/TL | LOAD INDEX | SPEED SYMBOL | RIM | | INFLATED DIMENSIONS (NO LOAD) | | INFLATED DIMENSIONS (W/ LOAD) | | TREAD DEPTH (MM) | INFLATING PRESSURE (psi/bar) | LOAD CAPACITY PER TIRE (KG) | | | | | | | |
|--------------|----|-------|------------|--------------|-----------------|--------------------|-------------------------------|---------------------|-------------------------------|---------------------------|------------------|------------------------------|-----------------------------|------|--------|------|---------|------|------|------|
| | | | | | RECOM. (INCHES) | PERMITTED (INCHES) | SECTION WIDTH MIN-MAX | OUTER DIAMETER (MM) | DYNAMIC RADIUS CIRCLE (MM) | STATIC LOADED RADIUS (MM) | | | Speed (KM/H) | | | | | | | |
| | | | | | | | | | | | | | 10 | 15 | 20 | 25 | 30 | 40 | 50 | 65 |
| 10-16.5NHS | 8 | TL | 131 | A3 | 8,25 | - | 264 | 773 | 2242 | 356 | 17 | 54 | 2090 | 1950 | 1795 | 1660 | 1520 | - | - | - |
| 10.0/75-15.3 | 12 | TL | 126 | A8 | 9.00 | - | 264 | 780 | 2262 | 355 | 19 | 68 | 2125 | 1920 | 1850 | 1800 | 1770 | 1700 | - | - |
| 11.5/80-15.3 | 12 | TL | 135 | A8 | 9.00 | - | 290 | 867 | 2514 | 390 | 19 | 59 | 2725 | 2460 | 2375 | 2310 | 2265 | 2180 | - | - |
| 12-16.5NHS | 10 | TL | 142 | A3 | 9,75 | - | 307 | 831 | 2410 | 378 | 19 | 65 | 2835 | 2650 | 2440 | 2255 | 2065 | - | - | - |
| 10.5/80-18 | 12 | TL | 134 | A8 | W9 | W8 ; 9.00 | 274 | 907 | 2630 | 413 | 20 | 54 | 3055 | 2905 | 2734,8 | 2585 | 2440 | 2120 | - | - |
| 280/80-18 | 12 | TL | 134 | A8 | W9 | W8; W10 | 282 | 905 | 2625 | 412 | 20 | 54 | 3055 | 2905 | 2734,8 | 2585 | 2440 | 2120 | - | - |
| 16.0/70-20 | 14 | TL | 154 | A8 | 13 | 12SDC ; 13SDC ; 14 | 418 | 1097 | 3181 | 496 | 31 | 51 | 5400 | 5140 | 4840 | 4575 | 4315 | 3750 | - | - |
| 405/70-20 | 14 | TL | 154 | A8 | 13 | 12SDC ; 13SDC ; 14 | 418 | 1097 | 3181 | 496 | 31 | 51 | 5400 | 5140 | 4840 | 4575 | 4315 | 3750 | - | - |
| 16.5/85-28 | 12 | TL | 152 | A8 | W13L | W14L ; W15L | 417 | 1423 | 4127 | 648 | 27 | 38 | 4535 | 4315 | 4065 | 3845 | 3625 | 3150 | - | - |
| 480/80-26 | 12 | TL | 156 | A8 | DW15L | DW16L | 479 | 1428 | 4141 | 645 | 27 | 36 | 5760 | 5480 | 5160 | 4880 | 4600 | 4000 | - | - |
| 23.1-26 | 14 | TL | 166 | A8 | DW20B | - | 587 | 1580 | 4582 | 708 | 39 | 30 | 7560 | 7195 | 6775 | 6405 | 6040 | 5250 | - | - |
| 16.0/70-24 | 14 | TL | 152 | B | 13.00 | 13 SDC | 407 | 1178 | 3416 | 538 | 32 | 51 | - | - | - | - | - | - | 3550 | - |
| 16.0/70-24 | 14 | TL | 152 | B | 13.00 | 13 SDC | 407 | 1178 | 3416 | 538 | 32 | 65 | 5800 | - | - | - | - | - | - | - |
| 14.5-20 | 14 | TT | 143 | D | 11 | 11 SDC | 355 | 1095 | 3176 | 495 | 28 | 51 | - | 4715 | 4495 | 4305 | 4114,75 | 3705 | 3105 | 2725 |
| 14.5-20 | 14 | TL | 143 | D | 11 | 11 SDC | 355 | 1095 | 3176 | 495 | 28 | 51 | - | 4715 | 4495 | 4305 | 4114,75 | 3705 | 3105 | 2725 |
| 405/70-24 | 14 | TL | 152 | B | 13.00 | 13 SDC | 407 | 1178 | 3416 | 538 | 32 | 65 | 5850 | - | - | - | - | - | - | - |



Petlas