

IND 25

Deep grooved pattern provides high self cleaning feature. Extra rubber in its compound provides long wear life and comfortable drive on hard surfaces. Thanks to its multi-purpose gum and rubber structure, designed for small loaders with back-hoe and tele-handlers which are used on soft surfaces where extra traction power is needed, it is resistant to cuts, ruptures and cracks; and provides a long driving life and a comfortable drive.



INDUSTRIAL TRACTION IND 25

TIRE SIZE	PR	TT/TL	LOAD INDEX	SPEED SYMBOL	RIM		INFLATED DIMENSIONS (NO LOAD)		INFLATED DIMENSIONS (W/LOAD)		TREAD DEPTH (MM)	INFLATING PRESSURE (psi/bar)	LOAD CAPACITY PER TIRE (KG)					
					RECOM. (INCHES)	PERMITTED (INCHES)	SECTION WIDTH MIN-MAX	OUTER DIAMETER (MM)	DYNAMIC RADIUS CIRCLE (MM)	STATIC LOADED RADIUS (MM)			Speed (KM/H)					
													10	15	20	25	30	40
12.5/80-18	14	TL	146	A8	W9	11.00	308	987	2862	446	27	62	3750	3390	3270	3180	3120	3000
340/80-18	12	TL	142	A8	11	W10; W11	343	1001	2903	452	27	54	3315	2995	2890	2810	2755	2650
14.5-20	14	TT	143	D	11	11 SDC	355	1095	3176	495	28	51	4495	4085	3545	3350	3135	2890
14.5-20	14	TL	143	D	11	11 SDC	355	1095	3176	495	28	51	4495	4085	3545	3350	3135	2890
16.0/70-20	14	TL	154	A8	13	12SDC ; 13SDC ; 14	418	1075	3103	495	33	51	4690	4240	4090	3975	3900	3750
16.0/70-20	16	TL	156	A8	13	12SDC ; 13SDC ; 14	418	1075	3103	495	33	58	5000	4520	4360	4240	4160	4000
16.9-24	12	TL	149	A8	DW15L	DW14L	429	1310	3799	592	30	38	4065	3675	3545	3445	3380	3250
16.9-24	14	TL	152	A8	DW15L	DW14L	429	1310	3799	592	30	43	4440	4010	3870	3760	3690	3550
16.0/70-24	14	TL	152	B	13.00	13 (DC) - 13 (SDC)	407	1178	3405	542	34	51	-	3975	3905	3835	3765	3655
405/70-24	14	TL	152	B	13.00	13 (DC) - 13 (SDC)	407	1178	3405	542	34	51	-	3975	3905	3835	3765	3655
19.5L-24	12	TL	151	A8	DW16A	-	495	1314	3810	594	29	34	4315	3890	3760	3655	3590	3450
440/80-24	12	TL	149	A8	DW14L	DW13; DW13L; DW15L	441	1314	3810	594	30	38	4065	3675	3545	3445	3380	3250
16.5/85-24	12	TL	149	A8	W13L	W15L ; W14L	417	1322	3834	597	30	41	4065	3675	3545	3445	3380	3250
16.5/85-24	16	TL	156	A8	W13L	W15L ; W14L	417	1322	3834	597	30	54	5000	4520	4360	4240	4160	4000
16.9-28	12	TT	152	A8	DW15L	DW14L	429	1410	4089	643	30	38	4440	4012	3870	3765	3690	3550
16.9-28	12	TL	152	A8	DW15L	DW14L	429	1410	4089	643	30	38	4440	4012	3870	3765	3690	3550
16.9-28	14	TL	156	A8	DW15L	DW14L	429	1410	4089	643	30	44	5000	4520	4360	4240	4160	4000
440/80-28	12	TL	152	A8	DW14L	DW13; DW13L; DW15L	441	1415	4104	645	30	38	4440	4012	3870	3765	3690	3550
18.4-26	12	TL	156	A8	DW16L	DW15L	467	1425	4133	644	32	36	5000	4520	4360	4240	4160	4000
18.4-26	14	TL	158	A8	DW16L	DW15L	467	1425	4133	644	32	42	5310	4800	4630	4505	4420	4250
18.4-26	16	TL	160	A8	DW16L	DW15L	467	1425	4133	644	32	48	5625	5085	4905	4770	4680	4500
480/80-26	14	TL	158	A8	DW15L	DW16L	479	1428	4141	647	32	42	5310	4800	4630	4505	4420	4250



petlas