



NB 38

Resistant against cut and tears with bidirectional pattern and reinforced rubber structure.
Resistant against lateral impacts and cuts with extra reinforced rubber structure, especially on rocky surfaces



TIRE SIZE	PR	TT/ TL	LOAD INDEX		SPEED SYMBOL	RIM		INFLATED DIMENSIONS (NO LOAD)		INFLATED DIMENSIONS (W/ LOAD)		TREAD DEPTH (MM)	INFLATING PRESSURE (psi/bar)	LOAD CAPACITY PER TIRE (SINGLE AXE USAGE)	LOAD CAPACITY PER TIRE (DOUBLE AXE USAGE)
			SINGLE AXE USAGE	DOUBLE AXE USAGE		RECOM. (INCHES)	PERMITTED (INCHES)	SECTION WIDTH MIN-MAX	OUTER DIAMETER (MM)	DYNAMIC RADIUS CIRCLE (MM)	STATIC LOADED RADIUS (MM)			50	50
7.50-20	10	TT	123	122	B	5.50F	6.00F	214	904	2622	417	15	58	1550	1500
9.00-20	14	TT	140	137	B	7.00	6.5 ; 7.5	230	1036	3004	471	20	62	2500	2300
10.00-20	16	TT	146	143	B	7.50	7.0 ; 8.0	270	1060	3074	481	22	109	3000	2725

