

TA 130^{/70}

Harvester- Tractor
Radial

PERFORMANCE INFORMATION

General purpose R1W farm front and rear tire with standard profile and tread design for high power tractors and harvester



FEATURES

Long service life / Durability

- Strong carcass and impact ply
- Special tread compound provides high resistance against wear and cuts
- Tread profile provides high resistance against tread base fatigue and the tire maintains its traction performance even at its half-life

High Traction / Self Cleaning

- Special tread geometry provides self cleaning
- Strong and flexible sidewall
- Perfect grip/high traction with wide footprint

Low soil compaction / Reduced slip

- Special tread structure provides high traction and less sinking at soft surfaces
- Wide footprint provides lower soil compaction
- Ensures a balanced steering by reduced slip at all surfaces

SIZES 600/70 R28 • 600/70 R30 • 600/70 R34 • 710/70 R38 • 800/70 R38
620/70 R42 • 710/70 R42



Harvester - Tractor Radial • Characteristics of **TA 130^{/70}**

	Tire Size	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg				
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h				
											20	30	40	50	65
	600/70 R28	TL	161 D	DW20B	DW18L, W18L	591	1551	4653	692	29 / 2,0	4770	4460	4245	4070	3880
										32 / 2,2	4920	4600	4380	4200	4000
										35 / 2,4	5075	4745	4515	4330	4125
	600/70 R30	TL	158 D	DW20B	DW18L, W18L	591	1602	4806	717	29 / 2,0	4915	4595	4375	4195	3995
										32 / 2,2	5070	4740	4515	4330	4125
										35 / 2,4	5230	4890	4655	4465	4250
	600/70 R34	TL	160 D	DW18B	DW20L, W18L	591	1723	5169	776	29 / 2,0	5205	4865	4630	4440	4230
										32 / 2,2	5370	5020	4780	4585	4365
										35 / 2,4	5535	5175	4930	4725	4500
			171 D	DW23B	-	716	1959	5877	941	29 / 2,0	7110	6650	6330	6070	5780
										32 / 2,2	7340	6860	6530	6265	5965
										35 / 2,4	7565	7075	6735	6460	6150
	710/70 R38	TL	171 D	DW23B	-	716	1959	5877	941	29 / 2,0	7110	6650	6330	6070	5780
										32 / 2,2	7340	5860	6530	6265	5965
										35 / 2,4	7565	7075	6735	6460	6150
	800/70 R38	TL	178 D	DW25B	DW27B	795	2055	6090	905	29 / 2,0	8670	8110	7720	7260	7050
										32 / 2,2	8950	8365	7965	7495	7275
										35 / 2,4	9225	8625	8210	7725	7500
	620/70 R42	TL	166 D	DW20B	-	625	1971	5913	891	29 / 2,0	6130	5730	5455	5230	4980
										32 / 2,2	6325	5910	5630	5400	5140
										35 / 2,4	6520	6095	5805	5565	5300
	710/70 R42	TL	173 D	DW23B	-	716	2061	6183	891	29 / 2,0	7515	7030	6690	6415	6110
										32 / 2,2	7755	7250	6905	6620	6305
										35 / 2,4	7995	7475	7120	6825	6500

• Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

* For load capacity on various speed ratings, and inflation figures, please consult your sales representative.
** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.