

TA 60

Tractor Rear

PERFORMANCE INFORMATION

High traction R1 farm rear tire for standard field operations



FEATURES

Long service life / Durability

- Strong nylon carcass structure provides optimum durability
- Special tread compound provides high resistance against wear and cuts
- Tread profile provides high resistance to tread base fatigue

Ease of use

- Wide and strong body provides easy grip and high traction
- Special tread geometry provides efficient self-cleaning

SIZES

8.3-24 • 9.5-24 • 11.2-24 • 12.4-24 • 13.6-24 • 14.9-24 • 18.4-26 • 11.2-28 • 12.4-28
13.6-28 • 14.9-28 • 16.9-28 • 14.9-30 • 16.9-30 • 18.4-30 • 12.4-32 • 16.9-34 • 18.4-34
12.4-36 • 13.6-36 • 13.6-38 • 14.00-38 • 15.5-38 • 16.9-38 • 18.4-38

Tractor Rear • Characteristics of TA 60

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
8.3-24	8	TT	108 / A6	W7	W6	211	995	2965	455	36 / 2.7	1275	1185	1090	975	910	2305
										32 / 2.2	1320	1225	1130	1005	940	2375
										35 / 2.4	1400	1300	1200	1070	1000	2450
9.5-24	8	TT	112 / A6	W8	W7	24	1050	3129	481	33 / 2.3	1430	1325	1225	1095	1020	920
										36 / 2.5	1495	1385	1280	1065	1065	960
										41 / 2.8	1570	1455	1345	1120	1120	1010
11.2-24	8	TT	116 / A6	W10	W9	284	1105	3293	503	29 / 2.0	1630	1510	1395	1245	1165	1050
										32 / 2.2	1680	1560	1440	1290	1200	1080
										35 / 2.4	1750	1625	1500	1340	1250	1125
13.6-24	8	TT	123 / A6	DW12	DW11	345	1190	3576	541	25 / 1.7	2040	1895	1750	1560	1460	1310
										28 / 1.9	2085	1935	1790	1595	1490	1340
										29 / 2.0	2170	2015	1860	1660	1550	1395
12.4-24	6	TT	115 / A6	W11	W9, W10	315	1160	3457	525	20 / 1.4	1550	1440	1330	1185	1110	995
										22 / 1.5	1615	1500	1390	1235	1155	1040
										25 / 1.7	1700	1580	1460	1300	1215	1095
	8	TT	120 / A6							29 / 2.0	1860	1730	1600	1425	1330	1200
										32 / 2.2	1920	1785	1650	1470	1730	1235
										33 / 2.3	1960	1820	1680	1500	1800	1260
	12	TT	128 / A6							44 / 3.0	2345	2175	2010	1120	1675	1505
										46 / 3.2	2420	2245	2075	1155	1730	1555
										51 / 3.5	2520	2340	2160	1200	1800	1620

• Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

* For load capacity on various speed ratings, and inflation figures, please consult your sales representative.

** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.

Tractor Rear • Characteristics of TA 60

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
14.9-24	4	TL / TT	112 / A6	W13	W11, W12	378	1265	3770	567	-	-	-	-	-	-	
										10 / 0.7	1495	1385	1280	1140	1065	960
	12 / 0.8	1570	1455							1345	1200	1120	1010			
	15 / 1.0	1780	1650							1525	1361	1270	1145			
	17 / 1.2	1975	1835							1695	1510	1410	1270			
	20 / 1.4	2170	2015							1860	1660	1550	1395			
	22 / 1.5	2370	2200							2030	1810	1695	1525			
	23 / 1.6	2420	2245							2075	1850	1730	1555			
	26 / 1.8	2520	2340							2160	1925	1800	1620			
	35 / 2.4	2825	2620							2420	2160	2015	1815			
	39 / 2.7	2910	2700							2495	2225	2080	1875			
	43 / 3.0	2970	2755							2545	2270	2120	1910			
	41 / 2.8	3190	2965							2735	2445	2280	2050			
	46 / 3.2	3490	3240							2990	2670	2490	2245			
52 / 3.6	3710	3445	3180	2840	2650	2385										
18.4-26	12	TT/ TL	146 / A6	W16L	W15L	467	1450	4321	647	29 / 2.0	3990	3705	3420	3050	2850	2565
										32 / 2.2	4115	3825	3530	3145	2940	2645
										33 / 2.3	4200	3900	3600	3210	3000	2700
	35 / 2.4	4235	3930							3630	3240	3025	2720			
	38 / 2.6	4415	4100							3785	3380	3155	2840			
41 / 2.8	4550	4225	3900	3480	3250	2925										
11.2-28	8	TT	118 / A6	W10	W9	284	1205	3591	554	29 / 2.0	1720	1595	1475	1320	1230	1105
										32 / 2.2	1780	1645	1525	1360	1270	1140
										35 / 2.4	1850	1715	1585	1415	1320	1190
12.4-28	6	TT	117 / A6	W11	W9, W10	315	1260	3755	576	20 / 1.4	1640	1520	1405	1250	1170	1050
										22 / 1.5	1710	1590	1470	1305	1220	1100
										25 / 1.7	1800	1670	1545	1375	1285	1160
	29 / 2.0	1995	1855							1710	1525	1425	1285			
	32 / 2.2	2060	1910							1765	1575	1470	1325			
33 / 2.3	2100	1950	1800	1605	1500	1350										

• Load capacity on recommended speed and pressure is stated with dark colour.

Tractor Rear • Characteristics of TA 60

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)		Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
13.6-28	6	TT	121 / A6	W12	W11	345	1310	3904	596	20 / 1.4	1850	1715	1585	1415	1320	1190
										22 / 1.5	1950	1810	1670	1495	1395	1255
										23 / 1.6	2030	1885	1740	1555	1450	1305
	8	TT	125 / A6							25 / 1.7	2170	2015	1860	1660	1550	1400
										28 / 1.9	2265	2105	1940	1730	1620	1455
										29 / 2.0	2310	2145	1980	1765	1650	1485
14.9-28	6	TT	125 / A6	W13	W11, W12	378	1365	4068	618	17 / 1.2	2105	1955	1805	1610	1505	1350
										19 / 1.3	2195	2040	1880	1685	1570	1410
										20 / 1.4	2310	2145	1980	1770	1650	1485
	8	TT	130 / A6							22 / 1.5	2475	2300	2120	1895	1770	1590
										23 / 1.6	2610	2420	2235	1995	1865	1675
										26 / 1.8	2660	2470	2280	2035	1900	1710
16.9-28	8	TT	135 / A6	W15L	W14L	429	1435	4276	646	20 / 1.4	2780	2580	2380	2125	1985	1790
										22 / 1.5	2905	2695	2485	2220	2070	1865
										25 / 1.7	3055	2835	2615	2335	2180	1965
	10	TT	139 / A6							25 / 1.7	3200	2970	2740	2445	2285	2060
										26 / 1.8	3270	3035	2800	2500	2335	2100
										29 / 2.0	3405	3160	2915	2600	2430	2190
	12	TT	143 A6	29 / 2.0	3585	3330	3075	2740	2560	2305						
				32 / 2.2	3700	3435	3170	2830	2645	2375						
				35 / 2.4	3815	3540	3270	2915	2725	2450						
14.9-30	8	TT	131 / A6	W13	W11, W12	378	1415	4217	643	22 / 1.5	2540	2360	2180	1945	1815	1635
										23 / 1.6	2675	2485	2295	2050	1910	1720
										26 / 1.8	2730	2535	2340	2090	1950	1755
	10	TT	135 / A6							29 / 2.0	2905	2695	2490	2220	2070	1870
										32 / 2.2	2995	2780	2570	2290	2140	1925
										33 / 2.3	3055	2835	2620	2335	2180	1965

* Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

* For load capacity on various speed ratings, and inflation figures, please consult your sales representative.

** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.

Tractor Rear • Characteristics of TA 60

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
16.9-30	6	TT	130 / A6	W15L	W14L	429	1485	4425	671	15 / 1.0	2315	2150	1990	1770	1655	1490
										16 / 1.1	2420	2250	2075	1855	1730	1555
										19 / 1.3	2660	2470	2280	2035	1900	1710
	8	TT	137 / A6							20 / 1.4	2930	2725	2515	2240	2095	1885
										22 / 1.5	3060	2840	2625	2340	2185	1970
										25 / 1.7	3220	2990	2760	2460	2300	2070
	10	TT	139 / A6							29 / 2.0	3205	2970	2740	2445	2285	2060
										32 / 2.2	3340	3100	2860	2550	2380	2145
										35 / 2.4	3405	3160	2915	2600	2430	2190
	12	TT	143 / A6							29 / 2.0	3550	3300	3040	2715	2535	2285
										32 / 2.2	3665	3405	3140	2805	2615	2355
										35 / 2.4	3815	3545	3270	2920	2725	2455
14	TT	144 / A6	32 / 2.2	3650	3385	3125	2790	2605	2345							
			35 / 2.4	3765	3495	3225	2880	2690	2420							
			38 / 2.6	3920	3640	3360	3000	2800	2520							
18.4-30	6	TT	134 / A6	W16L	W15L	467	1550	4619	697	13 / 0.9	2705	2505	2315	2070	1930	1740
										15 / 1.0	2820	2620	2420	2160	2015	1815
										16 / 1.1	2970	2755	2545	2270	2120	1910
	8	TT	139 / A6							17 / 1.2	3100	2880	2660	2370	2210	1993
										19 / 1.3	3235	3000	2775	2470	2310	2080
										20 / 1.4	3405	3160	2920	2600	2430	2190
	10	TT	145 / A6							22 / 1.5	3780	3510	3240	2890	2700	2430
										23 / 1.6	3980	3695	3410	3045	2845	2560
										26 / 1.8	4060	3770	3480	3105	2900	2610
	12	TT	149 / A6							29 / 2.0	4325	4015	3705	3310	3090	2780
										32 / 2.2	4415	4100	3785	3380	3155	2840
										33 / 2.3	4550	4225	3900	3480	3250	2925
14	TT	151 / A6	33 / 2.3	4445	4130	3810	3400	3175	2860							
			36 / 2.5	4640	4310	3975	3550	3315	2980							
			39 / 2.7	4830	4485	4140	3695	3450	3105							

• Load capacity on recommended speed and pressure is stated with dark colour.

Tractor Rear • Characteristics of TA 60

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
12.4-32	8	TT	124 / A6	W11	W9, W10	315	1360	4053	626	29 / 2.0	2130	1975	1825	1630	1520	1370
										32 / 2.2	2195	2040	1885	1680	1570	1410
										33 / 2.3	2240	2080	1920	1715	1600	1440
16.9-34	8	TT	139 / A6	W15L	W14L	429	1585	4723	721	20 / 1.4	3100	2880	2655	2370	2210	1995
										22 / 1.5	3235	3005	2770	2470	2310	2080
										25 / 1.7	3405	3160	2915	2600	2430	2190
	10	TT	142 / A6							25 / 1.7	3380	3135	2990	2580	2410	2170
										26 / 1.8	3525	3275	3025	2695	2520	2270
										29 / 2.0	3710	3445	3180	2835	2650	2385
	12	TT	145 / A6							29 / 2.0	3860	3585	3305	2950	2755	2480
										32 / 2.2	3980	3695	3410	3045	2845	2560
										33 / 2.3	4060	3770	3480	3105	2900	2610
	14	TT	148 / A6							29 / 2.0	3705	3440	3175	2830	2650	2380
										33 / 2.3	4100	3810	3515	3135	2930	2640
										38 / 2.6	4410	4095	3780	3370	3150	2835
18.4-34	8	TT	141 / A6	W16L	W15L	467	1650	4917	747	17 / 1.2	3280	3050	2815	2510	2345	2110
										19 / 1.3	3425	3185	2940	2620	2450	2205
										20 / 1.4	3605	3350	3090	2755	2575	2320
	10	TT	146 / A6							22 / 1.5	3910	3630	3350	2985	2790	2510
										23 / 1.6	4115	3825	3530	3145	2940	2650
										26 / 1.8	4200	3900	3600	3210	3000	2700
	12	TT	151 / A6							29 / 2.0	4590	4260	3935	3510	3280	2950
										32 / 2.2	4735	4395	4060	3620	3380	3045
										33 / 2.3	4830	4485	4140	3695	3450	3105
	14	TT	156 / A6							29 / 2.0	4595	4265	3935	3510	3280	2955
										32 / 2.2	5210	4840	4465	3980	3720	3350
										35 / 2.4	5600	5200	4800	4280	4000	3600

• Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

* For load capacity on various speed ratings, and inflation figures, please consult your sales representative.

** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.

Tractor Rear • Characteristics of TA 60

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
12.4-36	8	TT	126 / A6	W11	W9, W10	315	1465	4366	678	29 / 2.0	2260	2100	1940	1730	1615	1455
										32 / 2.2	2335	2165	1995	1785	1670	1495
										33 / 2.3	2380	2210	2040	1820	1700	1530
13.6-36	6	TT	125 / A6	W12	W11	345	1515	4515	698	20 / 1.4	2100	1955	1800	1610	1500	1350
										22 / 1.5	2220	2060	1900	1700	1585	1430
										23 / 1.6	2310	2145	1980	1770	1650	1485
	8	TT	129 / A6							28 / 1.9	2460	2285	2110	1880	1760	1585
	29 / 2.0									2515	2335	2155	1920	1795	1615	
	32 / 2.2									2590	2405	2220	1980	1850	1665	
13.6-38	8	TT	131 / A6	W12	W11	345	1565	4664	723	25 / 1.7	2485	2310	2130	1905	1775	1600
										26 / 1.8	2595	2410	2225	1990	1855	1670
										29 / 2.0	2730	2535	2340	2090	1950	1755
14.00-38	8	TT	131 / A6	W12	W11	355	1570	4679	725	25 / 1.7	2485	2310	2130	1905	1775	1600
										26 / 1.8	2595	2410	2225	1990	1855	1700
										29 / 2.0	2730	2535	2340	2090	1950	1755
	10	TT	136 / A6							29 / 2.0	2980	2770	2555	2280	2130	1915
	32 / 2.2									3075	2860	2640	2355	2195	1980	
	33 / 2.3									3135	2915	2690	2400	2240	2015	
15.5-38	8	TT	133 / A6	W14L	-	394	1570	4679	725	22 / 1.5	2685	2495	2300	2050	1915	1725
										23 / 1.6	2830	2625	2425	2160	2020	1820
										26 / 1.8	2885	2680	2475	2205	2060	1855
	10	TT	138 / A6							28 / 1.9	3140	2920	2695	2400	2245	2020
	29 / 2.0									3205	2980	2750	2450	2290	2065	
	32 / 2.2									3305	3070	2835	2525	2360	2125	
	12	TT	142 / A6							32 / 2.2	4980	3485	2990	2665	2490	2240
										35 / 2.4	5195	3835	3115	2780	2595	2335
										38 / 2.6	5300	3710	3180	2835	2650	2385

• Load capacity on recommended speed and pressure is stated with dark colour.

Tractor Rear • Characteristics of TA 60

Tire Size	PR	TT/TL	Load / Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
16.9-38	8	TT	141 / A6	W15L	W14L	429	1685	5021	771	20 / 1.4	3280	3050	2815	2510	2345	2110
										22 / 1.5	3425	3185	2940	2615	2450	2200
										25 / 1.7	3605	3350	3090	2755	2575	2320
	10	TT	141 / A6							25 / 1.7	3570	3315	3060	2730	2550	2295
										26 / 1.8	3725	3460	3195	2850	2660	2395
										29 / 2.0	3920	3640	3360	3000	2800	2520
										29 / 2.0	5640	3950	3385	3015	2820	2540
										31 / 2.1	5880	4115	3530	3145	2940	2645
										33 / 2.3	6000	4200	3600	3210	3000	2700
18.4-38	8	TT	143 / A6	W16L	W15L	467	1750	5215	797	17 / 1.2	3475	3225	2980	2660	2480	2235
										19 / 1.3	3625	3370	3110	2775	2590	2335
										20 / 1.4	3815	3545	3270	2920	2725	2455
	10	TT	147 / A6							22 / 1.5	4090	3800	3505	3125	2920	2630
										23 / 1.6	4180	3880	3580	3195	2985	2685
										26 / 1.8	4305	4000	3690	3290	3075	2770

• Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

- * For load capacity on various speed ratings, and inflation figures, please consult your sales representative.
- ** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.