

TD 16

Tractor
Front

PERFORMANCE INFORMATION

Ideal tractor front tire with special tread design for field and short distance road usage



FEATURES

Long service life / Durability

- Strong nylon carcass structure provides optimum durability
- Improved tread compound provides high resistance against wear and cuts
- Strong center and shoulder design provides high resistance to side impacts and tread base fatigue

Ease of use

- Special tread geometry provides easy steering
- Flexible carcass structure prevents sinking.

Self cleaning

- Special tread design provides efficient self cleaning

SIZES 5.50-16 • 6.00-16 • 6.50-16 • 7.50-16 • 6.00-19 • 6.50-20 • 7.50-20

Tractor Front • Characteristics of TD 16

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
5.50-16	6	TT	86 / A6	4.00E	3.50D, 4.50E	150	710	2130	329	45 / 3.1	745	710	670	570	495	395
										49 / 3.4	775	735	695	595	515	415
										54 / 3.7	795	760	715	610	530	425
6.00-16	6	TT	88 / A6	4.50E	4.00E, 5.00F	165	735	2205	338	41 / 2.8	775	735	695	595	515	410
										45 / 3.1	825	790	745	635	550	440
										48 / 3.3	840	800	755	645	560	450
6.50-16	6	TT	91 / A6	4.50E	4.00E, 5K, 5.50F, 5.50F	175	760	2280	350	38 / 2.6	850	810	765	650	565	450
										42 / 2.9	915	875	825	705	610	485
										45 / 3.1	925	880	830	710	615	495
	8	TT	97 / A6	52 / 3.6	1005	960	905	770	670	535						
				61 / 4.2	1095	1045	985	840	730	585						
7.50-16	6	TT	98 / A6	5.50F	5.00F, 5K, 6.00F	205	805	2415	367	35 / 2.4	1050	1000	945	805	700	560
										38 / 2.6	1095	1045	985	840	730	585
										41 / 2.8	1125	1075	1015	865	750	600
	8	TT	103 / A6	45 / 3.1	1210	1150	1085	925	805	645						
				54 / 3.7	1250	1250	1180	1005	875	700						
6.00-19	6	TT	93 / A6	4.50E	4.00E, 5.00F	165	814	2442	378	41 / 2.8	900	860	810	690	600	480
										45 / 3.1	955	910	860	730	635	510
										48 / 3.3	975	930	880	750	650	520

• Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

- * For load capacity on various speed ratings, and inflation figures, please consult your sales representative.
- ** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.



Tractor Front • Characteristics of TD 16

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg					
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h					
											10	15	20	25	30	40
650-20	8	TT	108 / A6	5.00F	4.00E, 5.50F	175	865	2595	402	45 / 3.1	1395	1330	1255	1070	930	745
										49 / 3.4	1455	1385	1310	1115	970	775
										54 / 3.7	1500	1430	1350	1150	1000	800
	10	TT	115 / A6			165				54 / 3.7	1660	1580	1490	1270	1105	885
										58 / 4.0	1730	1650	1560	1325	1155	925
										62 / 4.3	1820	1735	1640	1400	1215	970
750-20	8	TT	108 / A6	5.50F	5.00F	205	915	2727	420	42 / 2.9	1380	1315	1245	1260	920	735
										45 / 3.1	1440	1375	1295	1105	960	770
										49 / 3.4	1500	1430	1350	1150	1000	800
	10	TT	115 / A6			214				49 / 3.4	1660	1580	1490	1270	1105	885
										54 / 3.7	1730	1650	1560	1325	1155	925
										58 / 4.0	1820	1735	1640	1400	1215	970

• Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

* For load capacity on various speeds, and inflation figures, please consult your sales representative.

** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.

