

UN1 5 Rib

Trailer

PERFORMANCE INFORMATION

Modern harvester and trailer tire for fields and short distance roads



FEATURES

Long life

- Durable nylon carcass structure
- Deep / wide 5 rib tread design on the center
- Strong tread on shoulders
- High resistance against cuts and tread wear thanks to special tread compound.

Perfect load capacity / Ultimate performance

- Strong carcass structure
- Strong tread on shoulders
- It prevents from slide to sides and sinking to the ground with its wide tread design and high load capacity, and provides a balanced drive.

SIZES

19.0/45-17 • 500/50-17 • 15.0/55-17 • 400/60-15.5 • 10.5/65-16 • 340/55-16 • 13.0/65-18 • 10.0/75-15.3 RF
10.0/75-15.3 • 11.5/80-15.3 RF • 11.5/80-15.3 • 12.5/80-15.3 RF • 12.5/80-15.3 • 340/55-16 • 10.5/80-18

Trailer Characteristics of UN 1⁵ Rib

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg			
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h			
											10	30	40	50
19.0/45-17	12	TL	141/A8	16.00	-	491	866	2615	388	40 / 2.8	3070	2520	2290	2015
										46 / 3.2	3280	2690	2445	2150
										48 / 3.3	3450	2830	2575	2265
500/50-17	10	TL	143/A8	16.00	-	503	932	2846	420	23 / 1.6	3005	2550	2315	2015
										26 / 1.8	3220	2730	2480	2155
										29 / 2.0	3540	3000	2725	2370
	35 / 2.4	3595	2930							2665	2315			
	14	TL	149/A8							38 / 2.6	3905	3180	2890	2515
										41 / 2.8	4390	3575	3250	2825
15.0/55-17	14	TL	137/A8	13.00	13	391	850	2467	370	40 / 2.8	2490	2050	1860	1640
										46 / 3.2	2710	2225	2025	1780
										52 / 3.6	3080	2530	2300	2025
400/60-15.5	14	TL	145/A8	AG13.00	-	404	874	2661	390	40 / 2.8	3145	2580	2350	2060
										46 / 3.2	3380	2775	2520	2215
										52 / 3.6	3885	3190	2900	2550
10.5/65-16	10	TT	123/A8	W9	W8-W8L	274	755	2302	345	46 / 3.2	1745	1895	1720	1515
										52 / 3.6	1930	2065	1335	1650
										55 / 3.8	2075	1705	1550	1365
340/55-16	12	TL	140/A8	11	-	343	780	2325	735	49 / 3.4	3045	2435	2170	1955
										52 / 3.6	3185	2550	2275	2045
										58 / 4.0	3500	2800	2500	2250

* Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

* For load capacity on various speed ratings, and inflation figures, please consult your sales representative.

** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.

Trailer Characteristics of **UN 1⁵ Rib**

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg			
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h			
											10	30	40	50
13.0/65-18	12	TT	138/A8	11	-	336	890	2828	420	40 / 2.8	2580	2100	1910	1680
										46 / 3.2	2800	2285	2075	1825
										52 / 3.6	3185	2595	2360	2075
	14	TT	141/A8							50 / 3.6	2945	2435	2215	1945
										58 / 4.0	3150	2605	2370	2085
										63 / 4.3	3425	2830	2575	2265
10.0/75-15.3 REINFORCED	10	TL	123/A8	9.00	-	264	760	2368	352	46 / 3.2	1745	1430	1300	1145
										52 / 3.6	1910	1570	1425	1255
										56 / 3.9	2075	1705	1550	1365
	12	TL	126/A8							52 / 3.6	1905	1550	1410	1240
										58 / 4.0	2110	1720	1565	1375
										68 / 4.7	2295	1870	1700	1495
10.0/75-15.3	10	TT	123/A8	9.00	-	264	760	2368	352	46 / 2.0	1745	1430	1300	1145
										52 / 4.0	1910	1570	1425	1255
										56 / 3.9	2075	1705	1550	1365
	12	TL	123/A8							52 / 3.6	1905	1550	1410	1240
										58 / 4.0	2110	1720	1565	1375
										68 / 4.7	2295	1870	1700	1495
	14	TL	130/A8							75 / 5.2	2190	2070	1950	1740
										84 / 5.8	2315	2190	2060	1840
										92 / 6.3	2465	2325	2190	1955
11.5/80-15.3 REINFORCED	12	TL	135/A8	9.00	-	290	845	2600	382	46 / 3.2	2275	1895	1720	1515
										52 / 3.6	2480	2065	1875	1650
										60 / 4.1	2880	2400	2180	1915

• Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

* For load capacity on various speeds, and inflation figures, please consult your sales representative.

** Load capacity on standard speed and weight

• Our company is entitled to make any change on any information in this catalogue, without further notice.

• This catalogue annuls all the previous catalogues

• All figures are for reference; our company is not responsible for printing errors.

Trailer • Characteristics of UN 1⁵ Rib

Tire Size	PR	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg									
				Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h									
											10	30	40	50						
11.5/80-15.3	12	TT	135/A8	9.00	-	290	845	2600	382	46 / 3.2	2275	1895	1720	1515						
										52 / 3.6	2480	2065	1875	1650						
										60 / 4.1	2880	2400	2180	1915						
	12	TL	135/A8							46 / 3.2	2275	1895	1720	1515						
										52 / 3.6	2480	2065	1875	1650						
										60 / 4.1	2880	2400	2180	1915						
12.5/80-15.3 REINFORCED	12	TL	139/A8	900	-	307	889	2571	378	40 / 2.8	2695	2215	2015	1775						
										46 / 3.2	2955	2430	2210	1945						
										54 / 3.7	3250	2670	2430	2135						
12.5/80-15.3	12	TL	139/A8							9.00	-	307	889	2650	390	40 / 2.8	2695	2215	2015	1775
																46 / 3.2	2955	2430	2210	1945
																54 / 3.7	3250	2670	2430	2138
	16	TL	144/A8	54 / 3.7	3225	2650	2408	2120												
				60 / 4.1	3525	2895	2632	2315												
				71 / 4.9	3750	3080	2800	2465												
10.5/80-18	10	TT	131/A8	W9	W8-9	274	885	2768	412	40 / 2.8	2185	1780	1620	1420						
										46 / 3.2	2395	1950	1775	1560						
										54 / 3.7	2635	2145	1950	1715						
	12	TT	137/A8							46 / 3.2	2495	2050	1865	1640						
										52 / 3.6	2680	2200	2000	1760						
										60 / 4.1	3080	2530	2300	2020						
										50 / 3.6	2665	2185	1985	1750						
										58 / 4.0	2840	2330	2120	1865						
										65 / 4.5	3550	2915	2650	2330						
										14	TT	142/A8								

* Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

- * For load capacity on various speed ratings, and inflation figures, please consult your sales representative.
- ** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.