



COMPACTOR TYRES

- Speedways compactor tyres are engineered to provide even distribution of ground pressure & to give optimum compaction.
- Tread compound specially formulated to endure high temperatures and minimize loose materials sticky to tyres.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		LOAD CAPACITY				INFLATION PRESSURE		LOAD INDEX	SPEED	
									8KPH MAX LOAD		16KPH MAX LOAD					kmph	mph
			inch		mm	inch	mm	inch	kg	lbs	bar	psi					
7.50-15	ROADKING	6	6.0	TT	226	8.9	790	31.1	1770	1415	3894	3113	3.8	55	121	A3/15 kmph	A3/9mph
	ROADKING	14	6.0	TT	226	8.9	790	31.1	2860	2300	6292	5060	8.6	125	137	A3/15 kmph	A3/9mph
8.5/90-15K	ROADKING	14	6.0	TL	231	9.1	785	30.9	4060	2200	8932	7150	3.4	50	121	A3/15 kmph	A3/9mph
9.00-20	ROADKING	12	7.0	TT	274	10.8	1016	40.0	4420	3550	9724	7810	6.3	90	152	A3/15 kmph	A3/9mph
	ROADKING	14	7.0	TT	274	10.8	1016	40.0	4820	3850	10604	8481	7.3	104	155	A3/15 kmph	A3/9mph
11.00-20	ROADKING	16	8.0	TT	305	12.0	1082	42.6	5440	4350	11968	9570	7.3	104	159	A3/15 kmph	A3/9mph
	ROADKING	18	8.0	TT	305	12.0	1082	42.6	5900	4730	12980	10406	8.5	120	162	A3/15 kmph	A3/9mph



GRADER TYRES

- Rugged sturdy tyres for drive wheels of off-the-road equipment.
- Tough carcass and special trade compound with weather & ozone resistant properties to withstand cuts, snags & bruises in the most severe operating conditions.
- An open spaced traction pattern with self cleaning property provides traction capability, ideally suited for graders.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
																				kmph	mph
			inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi			
13.00-24	POWERGRIP G-2	12	8.0	TL	340	13.4	1280	50.4	584	23.0	3785	149.0	25	31	2725	5995	3.1	44	143	A8/40 kmph	A8/25mph
	POWERGRIP G-2	16	8.0	TL	340	13.4	1280	50.4	584	23.0	3785	149.0	25	31	3250	7150	4.1	58	149	A8/40 kmph	A8/25mph
	MONSTER	16	8.0	TL	340	13.4	1280	50.4	584	23.0	3785	149.0	34	42	3250	7150	4.1	58	149	A8/40 kmph	A8/25mph
14.00-24	POWERGRIP G-2	12	10.0	TL	375	14.7	1350	53.1	610	23.0	4013	158.0	25	31	3075	6750	2.8	40	147	A8/40 kmph	A8/25mph
	POWERGRIP G-2	16	10.0	TL	375	14.7	1350	53.1	610	24.0	4013	158.0	25	31	3650	8030	3.8	54	153	A8/40 kmph	A8/25mph
	MONSTER	16	10.0	TL	375	14.7	1350	53.1	610	24.0	4013	158.0	34	42	3650	8030	3.8	54	153	A8/40 kmph	A8/25mph